



Material Safety Data Sheet

24 Hour Emergency:
CHEMTREC: 1-800-424-9300

Outside U.S. and Canada
Chemtrec: 202-483-7616

NOTE: CHEMTREC, CANUTEC and National
Response Center emergency numbers to be used only
in the event of chemical emergencies involving a
spill, leak, fire, exposure or accident involving
chemicals

Section 1 - Chemical Product / Company Information

Product Name: BLUE ACRYLIC LOW VOC TRAFFIC SAFETY PAINT
Revision Date: 01/08/2007
Identification Number: 22L-D010
Supercedes : 01/08/2007
Product Use/Class: 55
Supplier: Aexcel Corporation
Manufacturer: Aexcel Corporation
7373 Production Drive
7373 Production Drive
Mentor, OH 44060
Mentor, OH 44060
Preparer: Webb, Lorie

Section 2 - Composition / Information On Ingredients

<u>Chemical Name</u>	<u>CAS No.</u>	<u>Wt. %</u>	<u>ACGIH TLV-TWA</u>	<u>ACGIH TLV-STEL</u>	<u>OSHA PEL-TWA</u>	<u>OSHA PEL-CEILING</u>
ACETONE	67-64-1	19.	500	750	1000	
XYLENE (100%)	1330-20-7	3.	100	150	100	
AROMATIC PETROLEUM DISTILLATES	64742-94-5	2.	10	15	10	

Section 3 - Hazards Identification

Emergency Overview: Flammable liquid and vapor.

Effects Of Overexposure - Eye Contact: Direct eye contact may cause irritation.

Effects Of Overexposure - Skin Contact: Skin irritant.

Effects Of Overexposure - Inhalation: Inhalation may cause irritation to the respiratory tract (nose, mouth, mucous membranes).

Effects Of Overexposure - Ingestion: Harmful: may cause lung damage if swallowed.

Effects Of Overexposure - Chronic Hazards: Chronic exposure may cause nausea and vomiting, higher exposure causes unconsciousness.

Primary Route(s) Of Entry: Skin Contact, Skin Absorption, Inhalation, Ingestion, Eye Contact

Section 4 - First Aid Measures

First Aid - Eye Contact: Rinse with plenty of water.

First Aid - Skin Contact: Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes.

First Aid - Inhalation: Move to fresh air. Oxygen or artificial respiration if needed.

First Aid - Ingestion: Never give anything by mouth to an unconscious person. Do not induce vomiting without medical advice.

Section 5 - Fire Fighting Measures

Flash Point, F: -4 TCC

Extinguishing Media: Carbon Dioxide, Dry Chemical, Foam

Unusual Fire And Explosion Hazards: Remove all sources of ignition.

Special Firefighting Procedures: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

<u>Chemical Name</u>	<u>LEL</u>	<u>UEL</u>	<u>FLASH POINT F. DEG</u>	<u>AUTO-IGNITION TEMP. F DEG</u>
ACETONE	2.60	12.80	-4	869
XYLENE (100%)	1.00	7.00	84	867
AROMATIC PETROLEUM DISTILLATES	1.00	6.00	142	ND

Section 6 - Accidental Release Measures

Steps To Be Taken If Material Is Released Or Spilled: Soak up with inert absorbent material and dispose of as hazardous waste.

Section 7 - Handling And Storage

Handling: Containers of this material may be hazardous when emptied. Handle in accordance with good industrial hygiene and safety practice.

Storage: Harmful - Store away from foodstuffs.

Section 8 - Exposure Controls / Personal Protection

Engineering Controls: Local ventilation of emission sources may be necessary to maintain ambient concentrations below recommended exposure limits.

Respiratory Protection: In the case of respirable dust and/or fumes, use self-contained breathing apparatus.

Skin Protection: Impervious gloves.

Eye Protection: Safety glasses with side-shields.

Other protective equipment: Impervious clothing.

Hygienic Practices: Contaminated work clothing should not be allowed out of the workplace.

Section 9 - Physical And Chemical Properties

Odor:	Characteristic
Appearance:	Heavy Blue Liquid
Specific Gravity:	1.481
Physical State:	Liquid

(See section 16 for abbreviation legend)

<u>CHEMICAL NAME</u>	<u>VAPOR DENSITY</u>	<u>EVAPORATION RATE</u>	<u>BOILING POINT</u>	<u>VP mmHg</u>	<u>at DEG. F</u>
ACETONE	2.00	14.4	133	226.00	68
XYLENE (100%)	3.70	0.70	279	7.00	68
AROMATIC PETROLEUM DISTILLATES	4.00	116.0	240	1.00	68

Section 10 - Stability And Reactivity

Conditions To Avoid: Avoid heat, sparks, open flame and other ignition sources.

Incompatibility: Keep away from strong oxidizing agents, heat and open flames.

Hazardous Decomposition Products: Carbon Monoxide, Carbon Dioxide

Hazardous Polymerization: Will not occur.

Stability: Stable

Section 11 - Toxicological Information

No Data.

Section 12 - Ecological Information

Ecological Information: Do not allow material to contaminate ground water system.

Section 13 - Disposal Information

Disposal Information: Contact waste disposal services. Do not flush into surface water or sanitary sewer system.

Section 14 - Transportation Information

DOT Proper Shipping Name: Paint, Flammable Liquid
 DOT Hazard Class: 3
 DOT UN/NA Number: 1263

Packing Group: III
 Resp. Guide Page: 128

Section 15 - Regulatory Information

CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

SARA Section 312:

Chemical Name

ACETONE
 XYLENE (100%)
 AROMATIC PETROLEUM DISTILLATES

CAS Number

67-64-1
 1330-20-7
 64742-94-5

SARA Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund

Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

Chemical Name

XYLENE (100%)

CAS Number

1330-20-7

Toxic Substances Control Act:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

Chemical Name

AROMATIC PETROLEUM DISTILLATES

1,2,4 TRIMETHYLBENZENE

CAS Number

64742-94-5

95-63-6

U.S. State Regulations: As follows -

California Proposition 65:

Warning: The following ingredients present in the product are known to the state of California to cause Cancer:

Chemical Name

ETHYL BENZENE

CAS Number

100-41-4

Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

None

International Regulations: As follows -

CANADIAN WHMIS:

This MSDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

CANADIAN WHMIS CLASS:

Section 16 - Other Information

HMIS Ratings:

Health: 2

Flammability: 3

Reactivity: 0

Personal Protection:

VOLATILE ORGANIC COMPOUNDS, GR/LTR: 141.48

REASON FOR REVISION:

Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

The information contained on this MSDS has been checked and should be accurate. However, it is the responsibility of the user to comply with all Federal, State, and Local laws and regulations.