



# Material Safety Data Sheet

24 Hour Emergency:  
CHEMTREC: 1-800-424-9300

Outside U.S. and Canada  
Chemtrec: 202-483-7616

NOTE: CHEMTREC, CANUTEC and National Response Center emergency numbers to be used only in the event of chemical emergencies involving spill, leak, fire, exposure or accident involving chemicals

## Section 1 - Chemical Product / Company Information

Product Name: WHITE ACRYLIC LOW VOC TRAFFIC SAFETY PAINT - OTC  
 Identification Number: 22W-D015  
 Product Use/Class: 55  
 Supplier: Aexcel Corporation  
 7373 Production Drive  
 Mentor, OH 44060  
 Preparer: Webb, Lorie

Revision Date: 04/01/2010  
 Supersedes : 04/01/2008  
 Manufacturer: Aexcel Corporation  
 7373 Production Drive  
 Mentor, OH 44060

## Section 2 - Composition / Information On Ingredients

<u>Chemical Name</u>	<u>CAS No.</u>	<u>Wt. %</u>	<u>ACGIH TLV-TWA</u>	<u>ACGIH TLV-STEL</u>	<u>OSHA PEL-TWA</u>
ACETONE	67-64-1	18.	500	750	1000
AROMATIC PETROLEUM DISTILLATES	64742-94-5	4.	10	15	10
TOLUENE	108-88-3	2.	50	150	100
DIISONONYL PHTHALATE	68515-48-0	1.	N/E	N/E	N/E

## Section 3 - Hazards Identification

Emergency Overview: Flammable liquid and vapor. Under normal use conditions, this product is not expected to cause adverse health effects.

Effects Of Overexposure - Eye Contact: Direct eye contact may cause irritation.

Effects Of Overexposure - Skin Contact: Direct skin contact may cause irritation. Skin irritant.

Effects Of Overexposure - Inhalation: Prolonged, repeated, or high concentrations may cause intense irritation to the respiratory tract (nose, mouth, mucous membranes). Inhalation may cause irritation to the respiratory tract (nose, mouth, mucous membranes).

Effects Of Overexposure - Ingestion: Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Harmful: may cause lung damage if swallowed.

Effects Of Overexposure - Chronic Hazards: Chronic exposure may cause nausea and vomiting, higher exposure causes unconsciousness.

Primary Route(s) Of Entry: Skin Contact, Skin Absorption, Inhalation, Ingestion, Eye Contact

## Section 4 - First Aid Measures

First Aid - Eye Contact: In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Rinse with plenty of water.

First Aid - Skin Contact: Wash off immediately with soap and plenty of water. If skin irritation persists, call a physician. Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes.

First Aid - Inhalation: In case of shortness of breath, give oxygen. Move to fresh air in case of accidental inhalation of vapors or decomposition products. Move to fresh air. Oxygen or artificial respiration if needed.

First Aid - Ingestion: Never give anything by mouth to an unconscious person. Call a physician or Poison Control Center immediately. Consult a physician. Do not induce vomiting without medical advice.

## Section 5 - Fire Fighting Measures

Flash Point, F: -4 Deg. TCC

Extinguishing Media: Carbon Dioxide, Dry Chemical, Foam

Unusual Fire And Explosion Hazards: Remove all sources of ignition.

Special Firefighting Procedures: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

<u>Chemical Name</u>	<u>LEL</u>	<u>UEL</u>	<u>FLASH POINT F. DEG</u>	<u>AUTO-IGNITION TEMP. F DEG</u>
ACETONE	2.60	12.80	-4	869
AROMATIC PETROLEUM DISTILLATES	1.00	6.00	142	ND
TOLUENE	1.00	7.00	45	896
DIISONONYL PHTHALATE	1.00	4.50	470	ND

## Section 6 - Accidental Release Measures

Steps To Be Taken If Material Is Released Or Spilled: Soak up with inert absorbent material and dispose of as hazardous waste.

## Section 7 - Handling And Storage

Handling: Containers of this material may be hazardous when emptied. Handle in accordance with good industrial hygiene and safety practice.

Storage: Harmful - Store away from foodstuffs.

## Section 8 - Exposure Controls / Personal Protection

Engineering Controls: Local ventilation of emission sources may be necessary to maintain ambient concentrations below recommended exposure limits.

Respiratory Protection: In the case of respirable dust and/or fumes, use self-contained breathing apparatus.

Skin Protection: Impervious gloves.

Eye Protection: Safety glasses with side-shields.

Other protective equipment: Wear suitable gloves and eye/face protection. Impervious clothing.

Hygienic Practices: Contaminated clothing should be changed and washed before reuse. Eating, drinking and smoking in immediate work area should be prohibited. Keep working clothes separately. General industrial hygiene practice. Contaminated work clothing

should not be allowed out of the workplace.

## Section 9 - Physical And Chemical Properties

Odor: Characteristic  
 Appearance: Heavy White Liquid  
 Specific Gravity: 1.532  
 Physical State: Liquid

(See section 16 for abbreviation legend)

CHEMICAL NAME	VAPOR DENSITY	EVAPORATION RATE	BOILING POINT	VP mmHg	at DEG. F
ACETONE	2.00	14.40	133	226.00	68
AROMATIC PETROLEUM DISTILLATES	4.00	116.00	NA	1.00	68
TOLUENE	3.20	2.00	233	16.70	68
DIISONONYL PHTHALATE	NA	NA	485	1.30	68

## Section 10 - Stability And Reactivity

Conditions To Avoid: Avoid heat, sparks, open flame and other ignition sources.

Incompatibility: Keep away from strong oxidizing agents, heat and open flames.

Hazardous Decomposition Products: Carbon Monoxide, Carbon Dioxide

Hazardous Polymerization: Will not occur.

Stability: Stable under normal conditions.

## Section 11 - Toxicological Information

No Data.

## Section 12 - Ecological Information

Ecological Information: Do not allow material to contaminate ground water system.

## Section 13 - Disposal Information

Disposal Information: Contact waste disposal services. Do not flush into surface water or sanitary sewer system.

## Section 14 - Transportation Information

DOT Proper Shipping Name: Paint, Flammable Liquid	Packing Group: II
DOT Hazard Class: 3	Resp. Guide Page: 128
DOT UN/NA Number: 1263	

## Section 15 - Regulatory Information

CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the

Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Chronic Health Hazard

SARA Section 312:

<u>Chemical Name</u>	<u>CAS Number</u>
ACETONE	67-64-1
AROMATIC PETROLEUM DISTILATES	64742-94-5
TOLUENE	108-88-3
DIISONONYL PHTHALATE	68515-48-0

SARA Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

<u>Chemical Name</u>	<u>CAS Number</u>
TOLUENE	108-88-3

Toxic Substances Control Act:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

None

U.S. State Regulations: As follows -

California Proposition 65:

Warning: The following ingredients present in the product are known to the state of California to cause Cancer:

None

Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

<u>Chemical Name</u>	<u>CAS Number</u>
TOLUENE	108-88-3

International Regulations: As follows -

CANADIAN WHMIS:

This MSDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

CANADIAN WHMIS CLASS:

## Section 16 - Other Information

### HMIS Ratings:

Health: 2                      Flammability: 3                      Reactivity: 0                      Personal Protection:

VOLATILE ORGANIC COMPOUNDS, GR/LTR: 146.18

### REASON FOR REVISION:

Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

The information contained on this MSDS has been checked and should be accurate. However, it is the responsibility of the user to comply with all Federal, State, and Local laws and regulations.